



DATA SHEET IV1260 Installation floor

Floor type: IV1260 Installation floor

DESCRIPTION:

Base plate: Self-centring pressure-distribution discs
Uprights: Hot-dip galvanised, gas pipe*
Connections: Head plate M20 including hammerhead screws
Bear profile: C-profile 60x60x2mm
Panels: At choice
Frames: C-profile 100x60x2mm

CONNECTIONS:

Steel uprights and a steel-framed grid of c-profiles, connected to one another with hammerhead screws, will form an electrically conductive structure. The Alteco installation floor system can therefore also be used for equipotential bonding, so that a copper earthing grid is superfluous to requirements (a measurement report drawn up by Kema is available).

GRID SIZES:

Grid sizes:	Maximum load:
1200x600mm:	$\leq 20,0 \text{ kN/m}^2$ (safety factor 1,35 NEN-EN 1993)
600x600mm:	$\geq 30,0 \text{ kN/m}^2$ (safety factor 2 NEN-EN 12825)

Or adjusted to layout or loads



SPECIFICATIONS:

Dimensions:
Depending on layout

Building height:
200-2500mm
(Adjustable $\pm 40\text{mm}$)

Weight:
(Grid size 1200x600mm,
building height 1000mm,
panels not included)
15 kg/m²

Grid size:
1200x600mm (standard)
Or adjusted to layout or loads.

Electrical conductive:
Yes, a KEMA report can be demonstrated

Surface material:
Panels at choice.

**3/4"pipe, 1"pipe or 5/4"pipe.
Depends on building height.*

CONTACT:

Alteco Europe BV

Radonstraat 4A
7031 GT WEHL
The Netherlands

T: +31 (0)314-365356

I: www.alteco.nl

E: info@alteco.nl